



## HART transparent repeater

### 9106B

- 24 VDC supply via power rail or connectors
- Active and passive mA input
- Active or passive output via the same two terminals
- Splitter function - 1 in and 2 out
- SIL3 Full Assessment and certified acc. to IEC 61508



#### Application

- 9106B is a 1- or 2-channel isolated 1:1 repeater barrier for intrinsic safety applications.
- The device supplies 2-wire SMART transmitters and can also be used for 2-wire SMART current sources. HART & BRAIN protocols are supported and are transferred bi-directionally.
- 9106B can be mounted in the safe area or in zone 2 / Cl. 1, div. 2 and receive signals from zone 0, 1, 2 and zone 20, 21, 22 including mining / Class I/II/III, Div. 1, Gr. A-G.
- For duplication/migration purposes, the outputs can be sent to two different DCS/PLC/HMI or any monitoring system.
- In safety applications (SIL loops), the 9106BxB can be used as a splitter with the following output configuration:
  - When using 9106BxB in a SIL2 safety function, channel 1 is used for the safety loop. Channel 2 can be used for any non-safety device.
  - For higher safety purposes (SIL 3), 9106BxB can be used as a splitter for SIL 3 loops. Channel 1 and 2 are then connected to the same safety PLC, where channel 2 is used as a redundant diagnostic channel. (for more information, consult the FMEDA Report and the Safety Manual).

#### Advanced features

- The PR 4501 detachable display and the green and red front LEDs indicate operation status for each channel.
- Monitoring of error events and cable breakage on input via the individual status relay and/or a collective electronic signal via the power rail.

#### Technical characteristics


- High galvanic isolation of 2.6 kVAC.
- Fast response time <5 ms
- High accuracy better than 0.1%.
- 2-wire transmitter supply >16 V.

#### Mounting


- The devices can be mounted vertically or horizontally without distance between neighboring units.

#### Applications


##### Input signals:




##### Output signals:




##### Power rail



##### Channel 2



##### Power connection:



Zone 0, 1, 2, 20, 21, 22, M1 & Cl. I/II/III, Div. 1 gr. A-G

Same power rail as above

Zone 2 & Cl. 1, Div. 2, gr. A-D or Safe Area

**Order:**

Type	Barrier version	Unit channels
9106B	U <sub>o</sub> = 28 V	: 1 Single : A
	U <sub>o</sub> = 25.6 V	: 2 Double : B

**Environmental Conditions**

Operating temperature.....	-20°C to +60°C
Storage temperature.....	-20°C to +85°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree.....	IP20
Installation in.....	Pollution degree 2 & measurement / overvoltage cat. II

**Mechanical specifications**

Dimensions (HxWxD).....	109 x 23.5 x 104 mm
Dimensions (HxWxD) w/ 4501 / 4511.....	109 x 23.5 x 116 / 131 mm
Weight approx.....	250 g
Weight incl. 4501 / 4511 (approx.).....	265 g / 350 g
DIN rail type.....	DIN EN 60715/35 mm
Wire size.....	0.13...2.08 mm <sup>2</sup> AWG 26...14 stranded wire
Screw terminal torque.....	0.5 Nm
Vibration.....	IEC 60068-2-6
2...13.2 Hz.....	±1 mm
13.2...100 Hz.....	±0.7 g

**Common specifications****Supply**

Supply voltage.....	19.2...31.2 VDC
Fuse.....	1.25 A SB / 250 VAC
Max. required power.....	≤ 1.1 W / ≤ 1.9 W (1 ch. / 2 ch.)
Max. power dissipation, 1 / 2 ch.....	≤ 0.8 W / ≤ 1.2 W

**Isolation voltage**

Test /working: Input to any.....	2.6 kVAC / 300 VAC reinforced isolation
Analog output to supply.....	2.6 kVAC / 300 VAC reinforced isolation
Status relay to supply.....	1.5 kVAC / 150 VAC reinforced isolation

**Response time**

Response time (0...90%, 100...10%).....	< 5 ms
SMART bi-directional communication frequency range.....	0.5...7.5 kHz
Signal / noise ratio.....	> 60 dB
Accuracy.....	Better than 0.1% of sel. range
mA, absolute accuracy.....	≤ ±16 µA
mA, temperature coefficient.....	≤ ±1.6 µA / °C
Effect of supply voltage change on output (nom. 24 VDC).....	< ±10 µA
EMC immunity influence.....	< ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst.....	< ±1% of span

**Input specifications****Current input**

Measurement range.....	3.5...23 mA
2-wire transmitter supply 9106B1x (U <sub>o</sub> = 27.5 VDC).....	>16 V / 20 mA
2-wire transmitter supply 9106B2x (U <sub>o</sub> = 25.3 VDC).....	>15 V / 20 mA
Sensor error detection: Loop break 4...20 mA.....	< 1 mA
Input voltage drop, supplied unit.....	< 4 V @ 23 mA

Input voltage drop, non-supplied unit.....	< 6 V @ 23 mA
--	---------------

**Output specifications****Current output**

Signal range.....	3.5...23 mA
Load (@ current output).....	≤ 600 Ω
Load stability.....	≤ 0.01% of span / 100 Ω
Current limit.....	≤ 28 mA

**Passive 2-wire mA output**

Effect of external 2-wire supply voltage variation.....	< 0.005% of span / V
Max. load resistance [Ω].....	(V <sub>supply</sub> -3.5)/0.023 A
Max. external 2-wire supply.....	26 VDC

**Status relay**

Relay function.....	N.C.
Programmable low setpoint.....	0...29.9 mA
Programmable high setpoint.....	0...29.9 mA
Hysteresis for setpoints.....	0.1 mA
Max. voltage.....	110 VDC / 125 VAC
Max. current.....	0.3 ADC / 0.5 AAC
Max. voltage - hazardous installation.....	32 VDC / 32 VAC
Max. current - hazardous installation.....	1 ADC / 0.5 AAC

of span.....	= normal measurement range
	4...20 mA

**Observed authority requirements**

EMC.....	2014/30/EU
LVD.....	2014/35/EU
RoHS.....	2011/65/EU
EAC.....	TR-CU 020/2011

**Approvals**

ATEX 2014/34/EU.....	DEKRA 11ATEX0244 X
IECEx.....	DEK 11.0084X
FM.....	0003044327-C
INMETRO.....	DEKRA 16.0001X
UL.....	UL 61010-1
EAC Ex TR-CU 012/2011.....	RU C-DK.GB08.V.00410
DNV-GL Marine.....	Stand. f. Certific. No. 2.4
CCOE.....	P337349/1
SIL.....	SIL 2 / SIL 3 certified & fully assessed acc. to IEC 61508