



MS2000 | TOTAL TRIHALOMETHANE ANALYSER

October 2022 | D. 1-000059 V. 3.0

The **MS2000** is a highly sensitive on-line total trihalomethane analyser which helps water treatment operators optimise their process to meet local regulations. The MS2000 utilises a contactless measurement technique that greatly reduces maintenance requirements. Furthermore, the instrument does not require reagents, which keeps the ongoing running costs to a minimum

APPLICATIONS

- Analyse THMs post treatment
- Monitor THMs in the distribution network
- Monitor THMs post-chlorination for enhanced process control
- Swimming pools and water parks
- Monitoring THMs in Health, Defense and Industrial establishments

FEATURES AND BENEFITS

- NO REAGENTS: low running costs
 - The most cost effective solution
 - High sensitivity: ideal for potable water
 - No sensor contact with water
 - Low maintenance, no sensor cleaning
-
- ✓ No reagents or gases, low running costs
 - ✓ Low maintenance, no sensor cleaning
 - ✓ Hourly sampling with instant results
 - ✓ Wide range of operating temperatures
 - ✓ Low cost of ownership



TECHNICAL SPECIFICATION

PARAMETER	OPERATIONAL REQUIREMENTS		NOTES
	MINIMUM	MAXIMUM	
DETECTION RANGE	5 ppb	1,000 ppb	
DISPLAY RANGE (DEFAULT)	0 ppb	200 ppb	Configurable on commissioning
REPEATABILITY	-2%	+2%	See Note 1
ACCURACY	-10%	+10%	See Note 1
MEASUREMENT FREQUENCY	60 minutes		Measurement reporting time 2 minutes
AMBIENT TEMPERATURE	0 °C	40 °C	See Note 2
WATER TEMPERATURE	1 °C	40 °C	See Note 2
ANALOGUE OUTPUT	4 mA	20 mA	Scalable to range required, max load 900 Ω
ANALOGUE OUTPUT ISOLATION	400 V DC		
RELAY VOLTAGE		50 V	Alarm and Fault Relays with NO and NC contacts
RELAY CURRENT		5 A	
SERVICE INTERFACE	On-screen -or USB-A to PC		Not available without touchscreen
DATA STORAGE	µSD Card		Instrument lifetime data stored
INSTRUMENT CASE	IP65		Coated Mild Steel
INSTRUMENT WEIGHT	16 kg		
SAMPLING CHAMBER MATERIAL	Stainless Steel		
SAMPLING SYSTEM WEIGHT	12 kg		Without water
SAMPLING SYSTEM DIMENSIONS	570 x 490 mm		
SAMPLING SYSTEM CAPACITY	3 litres		
FLOW LIMIT SWITCH	Contacts closed if flow below set point		Option available on request
WATER FLOW RATE	0.5 l/min	1.0 l/min	
SYSTEM DIMENSIONS	1170 x 490 x 300 mm		Mounted on 2 separate PVC backboards
SUPPLY VOLTAGE	90 V AC	240 V AC	50 Hz or 60 Hz
POWER CONSUMPTION	45 W		Typical 45 W during operation

NOTE 1: +/-10% from 30 to 1000 ppb, measured against a 100 ppb chloroform standard at standard temperature and pressure; Accuracy can be further improved at points of interest, using bespoke calibration. **NOTE 2:** Climate control might be needed depending on process and ambient conditions

CONSUMABLES

6 Months: Filters, Restrictor
As required: Air Pump, usually every 18-36 months

SERVICE

Service is necessary every 6 months to keep the instrument operating in optimal conditions. Service should be carried out by a trained technician who has undergone the standard Multisensor Systems training course.



PRINCIPLE OF OPERATION

The MS2000 utilises a contactless measurement technique based on Henry's Law, sensing headspace gases or volatiles in the sampling tank provided, and provides a measurement system with very low maintenance requirements.

Thanks to the clever design and technology the sensor never touches the water. This results in reduced drift, virtually no fouling, no sensor cleaning and very low maintenance.

The MS2000 is accurate to low ppb concentrations and its wide dynamic range allows it to be used in a wide variety of environments.

The concentration of **total trihalomethanes** (TTHMs) and water vapor in the headspace increases until equilibrium is reached with the concentration in the water.

A sample of gas is then taken from the headspace and the response analysed to provide a concentration in ppb of contaminants in the water.

For more information: *Total Trihalomethane Measurement using a Reagentless and Contactless Analyser developed by Multisensor Systems Ltd.*

ORDERING INFORMATION

Every MS2000 is shipped with the instrument and the sampling system already bolted on to their backboards, electronic manual and calibration certificate. Standard configuration of the instrument is 90 - 240 V AC.

Base Analyser

0-000026 MS2000 Total THM Analyser, 90 - 240 VAC, touchscreen display, 4-20 mA output and sampling system included

Common Accessories

7-000072 Profibus Module

7-000800 Modbus Module

Common Consumables

8-000153 Activated carbon filter assembly with AC

7-000799 Activated carbon pellets MS2000

7-000368 Gasket Bolt Down

7-000509 Fixed air flow restrictor

7-000504 In line filter 5µ

For a detailed quote get in touch with Multisensor Systems Ltd or an [approved distributor](#).

**HEAD OFFICE
(UNITED KINGDOM)**

Multisensor Systems Ltd.

Alexandra Court

Carrs Road

Cheadle

SK8 2JY

United Kingdom

T: +44 (0)161 491 5600

E: info@multisensor.co.uk



Multisensor Systems Limited reserves the right to revise any specifications and data contained within this document without notice.

Multisensor Systems is a developer and supplier of Water and Gas Analyzers specialising in oil in water, hydrocarbon analyzers, oil in water detectors, THM Analyzers and Ammonia Analyzers based in the United Kingdom.

The contents of this publication are provided to you "as is" without warranty of any kind, and are subject to change without notice. Multisensor systems does not assume any responsibility or liability for any damage, whether direct or indirect, relating to the use of this publication.

Multisensor Systems Ltd., Alexandra Court, Carrs Road, Cheadle, SK8 2JY, United Kingdom

©2022 Multisensor Systems Limited

CHANGELOG

MSS DOCUMENT CHANGE RECORD

Document Ref 1-000059

DATE	VERSION	CHANGED BY	CHECKED BY	ECN REF
03/11/2022	3.0	GO	BW,AM	1122-03